

BUILT TO OUTWORK

The #1 selling diesel pure utility vehicle in North America* grows with the addition of the new RTV-X1130. This long bed model holds true to the legacy of the RTV-X Series with the Kubota Diesel Engine, VHT-X transmission and hydraulic dump box and power steering that have made the X-Series so popular. With it comes a suite of new features like the long bed cargo box, ProKonvert functionality, and new cargo box accessories represent capability re-imagined. No matter what job you have to get done, or how you like to spend your free-time, the RTV-X1130 is built outwork! TOUGH & DEPENDABLE POWER YOUR PRODUCTIVITY CAPABILITY RE-IMAGINED


xiliao

TOUGH & DEPENDABLE



Full Steel Frame/CV Joint Guards

The high-rigidity steel frame isolates the occupants from noise, vibrations, and harshness. With structural strength that few in the industry can match, this durable frame can take years of punishment from heavy loads and rough terrain*. *See owner's manual for details.



VHT-X (Variable Hydraulic Transmission)

Kubota's VHT-X provides exceptional performance on various terrain with smooth and powerful acceleration. Low-speed driving is made exceptional through smooth throttle control, great traction and maneuverability with or without loads.



Wet Disk Brakes

The RTV-X series uses multi-disk wet brakes which provide long brake life. You'll also feel more secure, especially when traveling down long inclines, knowing that dynamic braking is helping to provide additional braking power and greater driving control.

POWER YOUR PRODUCTIVITY



6ft Long Cargo Bed

It's not enough to get you there and back. You need to get your stuff there and back, as well. This heavy-duty 6ft steel cargo bed can do that for you, carrying more than a half-ton (1212 lbs.) of tools, firewood, gear, supplies...whatever you need to haul from here to there and back again.





Standard Hydraulic Dump Bed

Dump sand, gravel, turf, or just about anything you can think of, from the RTV-X1130's whopping, 26.1 cu. ft. capacity cargo bed. Cargo that could take significant physical strength and time to unload can now be dumped with little effort in mere seconds.

Height Adjustable Suspension

Regardless of the terrain or load, independent suspension on all four wheels helps to ensure an exceptional ride. Kubota's Extra Duty IRS (Independent Rear Suspension) technology is durable and powers your productivity.

CAPABILITY RE-IMAGINED

Prokonvert Cargo Bed



Foldable Side Panel



Kubota

Tool-less Flatbed Conversion



Full Steel Cargo with Spray-on Bed Liner

GEAR UP AND CUSTOMIZE YOUR MACHINE



Tailgate Extender

Storage Box

Most existing Kubota accessories are compatible with the RTV-X1130.

SPECIFICATIONS

Model			RTV-X1130 Work Site	
Body color			Kubota Orange	RealTree®* AP Camouflage
	Make		KUBOTA D1105-E4-UV-2	
Engine	Туре		3-cylinders, 4-cycle, diesel, OHV	
	Displacement cu.in (cc)		68.5 (1123)	
	Horsepower** HP (kW)/rpm		24.8 (18.5)@3000	
Fuel tank capacity U.S.gals (<i>l</i>)		U.S.gals (<i>l</i>)	7.9 (30)	
Transmission			Variable hydro transmission (VHT-X)	
Max. Traveling speed mph (km/h)		mph (km/h)	25 (40)	
Wheels, drive system			4WD	
Front differential lock			Limited-slip differential	
Rear differential lock			Foot operated differential lock	
Gear selection			Hi-Lo range forward, Neutral, Reverse	
Drakas	Front / Rear		Wet-disk brake	
Brakes	Parking brake		Rear wheel, hand operated	
Steering			Hydrostatic power steering	
Suspension	Front / Rear		Dual A-Arms independent suspension	
Dimensions	Length in. (mm)		153 (3883)	
	Width	in. (mm)	63 (1605)
	Height, overall	in. (mm)	80 (2025)
	Front tread centers in. (mm)		50.4 (1280) (HDWS & ATV)	
	Rear tread centers in. (mm)		50.4 (1280) (HDWS & ATV)	
	Wheelbase in. (mm)		98.2 (2495)	
	Ground clearance front/rear in. (mm)		11.3 (285) / 9.4 (240)	
	Turning radius ft. (m)		17.1 (5.2)	
Towing capacity Ibs. (kg)		lbs. (kg)	1300 (590)	
Payload capacity lbs. (kg)		lbs. (kg)	1629 (739)	
Curb weight Ibs. (kg)		lbs. (kg)	2340 (1060)	
Cargo bed	Width	in. (mm)	54.5 (1384)	
	Length	in. (mm)	72.3 (1837)	
	Depth	in. (mm)	11.6 (294)	
	Volume	cu. ft. (m ³)	26.1 (0.74)	
	Bed height (no load)	in. (mm)	35.4 (900)	
	Load capacity	lbs. (kg)	1212 (550)	
	ProKonvert		Standard (Foldable/Removable Side Panel	with Tool-less Flatbed Conversion)
Tires	Front		25×10×12 HDWS, 6-PLY	
			25×10×12 ATV, 6-PLY	25×10×12 ATV, 6-PLY
	Rear		25×10×12 HDWS, 6-PLY	
			25×10×12 ATV, 6-PLY	25×10×12 ATV, 6-PLY
Wheels			Steel	
Front Guard			Standard Front Guard	Premium Front Guard
Hydraulic bed lift			Standard	
Spray-on Bed Liner			Standard	

*"Realtree®" is a registered trademark of Jordan Outdoor Enterprises, Ltd.

** SAE J1995

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seal betin alimotical all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.





1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: KubotaUSA.com

PIT 'FM ON

ROPS

KEEP 'EM O

<u>seatbei</u>