

## SSV SERIES SSV65



- Kubota Engine (Tier IV) with DPF
- Excellent 360 Visibility
- Sliding Front Door
- Spacious Cabin
- Reengineered Air Conditioning
- Telematics Available

**Dimensions:**  
Overall length: 135.4"  
Overall height: 79.9"  
Overall width: 66.5"

**Loader performance:**  
Rated operating capacity @ 50% of tipping load: 1,950 lbs.

**Operating weight (Rubber, canopy) (Open/closed):**  
7,099 / 7,319 lbs. (incl. operator's weight @ 165 lbs.)

**Engine:**  
Engine HP Gross (SAE J 1995):  
64 HP/47.7 kW / 2,700 rpm  
Displacement: 159.7 cu.in.

## SSV75



- Kubota Engine (Tier IV) with DPF
- Excellent 360 Visibility
- Sliding Front Door
- Spacious Cabin
- Reengineered Air Conditioning
- Telematics Available

**Dimensions:**  
Overall length: 144.1"  
Overall height: 81.3"  
Overall width: 71.8"

**Loader performance:**  
Rated operating capacity @ 50% of tipping load: 2,690 lbs.

**Operating weight (Rubber, canopy) (Open/closed):**  
8,245 / 8,466 lbs. (incl. operator's weight @ 165 lbs.)

**Engine:**  
Engine HP Gross (SAE J 1995):  
74.3 HP/55.4 kW / 2,600 rpm  
Displacement: 203.3 cu.in.

## SVL SERIES SVL65-2



- Kubota Engine (Tier IV) with DPF
- Advanced Multifunction Valve (AMV)
- Standard Self-leveling Function
- Low Ground Contact Pressure
- Spacious Cabin
- Sliding Front Door
- Reengineered Air Conditioning
- Telematics Available

**Dimensions:**  
Overall length: 136.4"  
Overall height: 79.9"  
Overall width: 65.2 / 67.6"

**Loader performance:**  
Rated operating capacity @ 35% of tipping load: 2,100 lbs.

**Operating weight (Rubber, canopy) (Open/closed):**  
8,135 / 8,631 lbs. (incl. operator's weight @ 165 lbs.)

**Engine:**  
Engine HP Gross (SAE J 1995):  
68.4 HP/51.0 kW / 2,600 rpm  
Displacement: 159.6 cu.in.

## SVL75-3 *New*



- Kubota Engine (Tier IV) with DPF
- Advanced Multifunction Valve (AMV)
- Standard Self-leveling Function
- Auto-downshift
- Improved Hinge Pin Height
- Keyless Engine Start
- Reversing Fan (Opt)
- One-piece Sealed and Pressurized Cab
- Sliding Front Door
- Wide-angle Rear View Camera
- Color LCD Touch Panel with Jog Dial
- Telematics Available

**Dimensions:**  
Overall length: 142.1"  
Overall height: 81.8"  
Overall width: 65.9 / 69.1"

**Loader performance:**  
Rated operating capacity @ 35% of tipping load: 2,490 lbs.

**Operating weight (Rubber, canopy) (Open/closed):**  
9,190 / 9,420 lbs. (incl. operator's weight @ 165 lbs.)

**Engine:**  
Engine HP Gross (SAE J 1995):  
74.3 HP/55.4 kW / 2,400 rpm  
Displacement: 203.2 cu.in.

## SVL97-2



- Kubota Engine with DPF & SCR
- Standard Self-leveling Function
- Standard Two-speed Travel
- Spacious Cabin
- Sliding Front Door
- Reengineered Air Conditioning
- Rear-view Camera
- Standard Kubota Telematics

**Dimensions:**  
Overall length: 154.6"  
Overall height: 83.3"  
Overall width: 77.2"

**Loader performance:**  
Rated operating capacity @ 35% of tipping load: 3,200 lbs.

**Operating weight (Rubber, canopy) (Open/closed):**  
11,277 / 11,552 lbs. (incl. operator's weight @ 165 lbs.)

**Engine:**  
Engine HP Gross (SAE J 1995):  
96.4 HP/71.9 kW / 2,400 rpm  
Displacement: 230.0 cu.in.

## An Office Fit for the Job

Kubota Compact Track Loaders offer spacious cabs with easy access, and that helps keep the operator out of the dust, dirt, and water. Add in our smooth hydraulic controls powered by a reliable Kubota engine and you've found a working environment that is a fit for almost any job.



## SVL75-3 NEW FEATURES

### One-Piece Sealed and Pressurized Cab

The new, one-piece cab is pressurized to prevent dirt, dust, rain and other debris from entering the cab. The pressurized design also reduces noise intrusion to keep you working long hours with minimal fatigue.

### Auto-shift

The auto-shift system enables automatic travel shift from high to low when turning in order to travel smoothly.



### Advanced Multifunction Valve (AMV)

The SVL75-3's hydraulic system features an innovative Advanced Multifunction Valve that provides smooth movements of all hydraulic functions when operated simultaneously. The AMV now allows operators to run the AUX hydraulics, bucket, and loader arm functions simultaneously without stalling.

### Faster Two-speed Travel

Shift from low gear at 5.6 mph (0.9 mph faster than the SVL75-2) to high gear at 8.6 mph (1.5 mph faster than the SVL75-2) to get the job done faster.

### LED Work Lights (Front & Rear)

LED Lights are brighter than halogen lights to let you get the job done in low-light conditions.

For Earth, For Life  
**Kubota**



Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/kW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

**KUBOTA TRACTOR CORPORATION**  
1000 Kubota Drive, Grapevine, TX 76051 Tel 817-756-1171 KUBOTA

Visit our web site at: [KubotaUSA.com](http://KubotaUSA.com)



Cat. No.8987A-01-US Printed in Japan '22-120, <img alt="recycling symbol" data-bbox="610 890 617 900"/>



**2023**

**KUBOTA CONSTRUCTION EQUIPMENT**

## KX SERIES

K008-5 / KX018-4 / KX030-4 / KX033-4  
KX040-4 / KX057-5 / KX080-4S2

## U SERIES

U10-5 / U17 / U27-4 / U35-4  
U48-5 / U55-5

## R SERIES

R430 / R540 / R640

## SSV SERIES

SSV65 / SSV75

## SVL SERIES

SVL65-2 / SVL75-3 / SVL97-2

## Reliable Kubota Designed Compact Excavators

That's because we focus on the customer's needs – power and performance, serviceability, operator comfort and reliability. Unlike most manufacturers, Kubota designs and manufactures the engines that go into our compact excavators, and into our other construction equipment as well. Kubota's involvement throughout the design and manufacturing process provides consistency and reliability. Make the smart choice for your business and invest in a Kubota.



### Always Improving Features

- Large cab door, operator's space
- Auto-downshift travel motors
- Up front control panel
- Float blade with BOE\*
- Auxiliary 1 diverter valve
- Improved A/C performance
- Single side engine servicing

\* BOE is for Angle Blade models only.

### Always Innovating

- Angle Blade
- 6 in 1 Blade

Note: Features are available for selected models.

**Kubota construction machines  
are chosen for a reason**

## KX SERIES

### K008-5

- Kubota Engine (Tier IV)
- Variable Track Gauge, Fits Through Standard Doorways
- Two Speed Travel
- AUX1 via Foot Pedal Control
- Operating Lock Lever
- 1 LED Working Light on the Boom
- TPSS
- Foldable ROPS
- Telematics Available



**Dimensions:**  
Overall length: 9'0"  
Overall height: 7'4"  
Overall width: 2'7" - 2'10"

**Working range:**  
Max. digging depth: 5'8"  
Max. digging radius @ ground: 9'11"  
Max. bucket breakout force: 2,205 lbf.

**Operating weight (Rubber, canopy):**  
2,315 lbs. (incl. operator's weight @ 165lbs.)

**Engine:**  
Engine HP Gross (SAE J 1995):  
10.3 HP / 2,050 rpm  
Displacement: 43.8 cu.in.

### KX018-4

- Kubota Engine (Tier IV)
- Enhanced Digging Force
- Extraordinary Stability and Lifting Capacity
- Variable Track Gauge, Fits Through Gates
- Auto-downshift Travel Motors
- Spacious Heated Cab (Opt)
- Digital Panel
- Telematics Available



**Dimensions:**  
Overall length: 12'2.1"  
Overall height: 7'11"  
Overall width: 7'7.7" / 7'8.5"  
Overall width: 3'3" - 4'3.2"

**Working range:**  
Max. digging depth: 7'9.7"  
Max. digging radius @ ground: 12'8"  
Max. bucket breakout force: 3,594 lbf.

**Operating weight (Rubber, canopy/cab):**  
3,737 / 3,957 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
16.1 HP / 2,300 rpm  
Displacement: 54.8 cu.in.

### KX030-4 *New*

- Kubota Engine (Tier IV)
- Powerful Breakout Force
- AUX1 Diverter Valve
- Spacious Cab (w/ Heater Opt)
- Deluxe Interior and Wide Entrance
- Meter panel positioned for easier access / visibility
- Auto-downshift Travel Motors
- Dozer Float Function
- Telematics Available



**Dimensions:**  
Overall length: 15'1.1"  
Overall height: 7'11"  
Overall width: 4'11"

**Working range:**  
Max. digging depth: 9'7"  
Max. digging radius @ ground: 15'9"  
Max. bucket breakout force: 6,924 lbf.

**Operating weight (Rubber, canopy/cab):**  
6,272 / 6,426 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
24.7 HP / 2,250 rpm  
Displacement: 100.5 cu.in.

### KX033-4

- Kubota Engine (Tier IV)
- Hydraulic Angle Blade w/BOE (Opt)
- AUX1 Diverter Valve
- Deluxe Interior and Wide Entrance
- Auxiliary Circuit 1
- Adjustable Max. Oil Flow Control
- Spacious Cab w/ Air Conditioning
- Auto-downshift Travel Motors
- Dozer Float Function
- Telematics Available



**Dimensions:**  
Overall length: 15'6"  
Overall height: 8'1.8"  
Overall width: 5'1"

**Working range:**  
Max. digging depth: 10'6"  
Max. digging radius @ ground: 16'10"  
Max. bucket breakout force: 8,138 lbf.

**Operating weight (Rubber, canopy/cab):**  
Standard blade: 7,420 / 7,742 lbs.  
Angle Blade: 7,781 / 8,104 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
24.8 HP / 2,200 rpm  
Displacement: 111.4 cu.in.

### KX040-4

- Kubota Engine (Tier IV) with DPF
- Automatic Regeneration System
- Hydraulic 6-in-1 Blade w/BOE (Opt)
- Hydraulic Angle Blade w/BOE (Opt)
- Dozer Float Function
- Spacious Cab
- Wider Entrance
- Fully Flat Floor
- Auxiliary Circuit 1 (2 as option)
- Adjustable Max. Oil Flow Control
- AUX1 Diverter Valve
- Auto-downshift Travel Motors
- Telematics Available



**Dimensions:**  
Overall length: 16'8.1"  
Overall height: 8'1.8"  
Overall width (Std. Angle Blade): 5'6.9"  
(6-in-1 Blade): 5'10.9"

**Working range:**  
Max. digging depth: 11'2.7"  
Max. digging radius @ ground: 17'9"  
Max. bucket breakout force: 9,535 lbf.

**Operating weight (Rubber, canopy/cab):**  
Standard blade: 9,195 / 9,500 lbs.  
Angle Blade: 9,545 / 9,855 lbs.  
6-in-1 Blade: 9,900 / 10,210 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995): 40.4 HP / 2,200 rpm  
Displacement: 111.4 cu.in.

### KX057-5

- Kubota Engine (Tier IV) with DPF
- Tight Tail Swing
- Hydraulic Angle Blade w/BOE (Opt)
- Auxiliary Circuit 1 (2 as option)
- AUX1 Diverter Valve
- Adjustable Max. Oil Flow Control
- Strong Bucket and Arm Breakout Force
- 7" Color Screen
- Keyless Start (Opt)
- Wider Cab w/ Air Conditioning
- Rear-view Camera (Opt)
- Auto-downshift Travel Motors
- Dozer Float Function
- Telematics Available



**Dimensions:**  
Overall length: 18'1"  
Overall height: 8'4"  
Overall width: 6'5"

**Working range:**  
Max. digging depth: 12'9"  
Max. digging radius @ ground: 20'1"  
Max. bucket breakout force: 10,172 lbf.

**Operating weight (Rubber, canopy/cab):**  
Standard blade: 12,346 / 12,577 lbs.  
Angle Blade: 12,820 / 13,051 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995): 47.6 HP / 2,200 rpm  
Displacement: 159.6 cu.in.

### KX080-4S2

- Kubota Engine (Tier IV) with DPF
- 2-pump Load Sensing Hydraulic System
- Hydraulic Angle Blade w/ BOE (Opt)
- Auxiliary Circuits (1 and 2)
- Adjustable Max. Oil Flow Control
- Auto-downshift Travel Motors
- Dozer Float Function
- Tight Tail Swing and Compact Machine Width
- Telematics Available



**Dimensions:**  
Overall length: 21'1.9"  
Overall height: 8'4"  
Overall width: 7'2.6"

**Working range:**  
Max. digging depth: 15'1.1"  
Max. digging radius @ ground: 23'6.3"  
Max. bucket breakout force: 14,860 lbf.

**Operating weight (Rubber, steel):**  
Standard blade: 18,596 / 18,706 lbs.  
Angle Blade: 19,456 / 19,566 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
66.6 HP / 2,000 rpm  
Displacement: 203.3 cu.in.

### U SERIES

### U10-5

- Kubota Engine (Tier IV)
- Variable Track Gauge, Fits Through Doorways
- Two Speed Travel
- AUX1 via Foot Pedal Control
- Hydraulic Lock System
- Hydraulic Pilot Control Side Levers
- 1 LED Working Light on the Boom
- TPSS
- Foldable ROPS
- Telematics Available



**Dimensions:**  
Overall length: 9'9"  
Overall height: 7'5"  
Overall width: 2'6" - 3'3"

**Working range:**  
Max. digging depth: 5'11"  
Max. digging radius @ ground: 10'11"  
Max. bucket breakout force: 2,337 lbf.

**Operating weight:**  
2,646 lbs. (incl. operator's weight @ 165lbs.)

**Engine:**  
Engine HP Gross (SAE J 1995):  
10.3 HP / 2,050 rpm  
Displacement: 43.8 cu.in.

## U SERIES

### U17

- Kubota Engine (Tier IV)
- Zero Tail Swing
- Large Pump Capacity
- Digital Panel
- Protected Motor Hoses
- Double-Flanged Track Roller & Short-pitched Rubber Crawler
- Variable Track Gauge, Fits Through Gates
- Telematics Available



**Dimensions:**  
Overall length: 11'7"  
Overall height: 7'8"  
Overall width: 3'3" - 4'1"

**Working range:**  
Max. digging depth: 7'7"  
Max. digging radius @ ground: 12'7"  
Max. bucket breakout force: 3,417.2 lbf.

**Operating weight:**  
3,693 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
16.1 HP / 2,300 rpm  
Displacement: 54.8 cu.in.

### U27-4

- Kubota Engine (Tier IV)
- Tight Tail Swing
- AUX1 Diverter Valve
- Deluxe Interior and Wide Entrance
- Proportional Flow Control of Auxiliary Circuit
- Spacious Cab (w/ Heater Opt)
- Auto-downshift Travel Motors
- Telematics Available



**Dimensions:**  
Overall length: 13'6"  
Overall height: 7'11"  
Overall width: 4'11"

**Working range:**  
Max. digging depth: 14'6"  
Max. digging radius @ ground: 15'4"  
Max. bucket breakout force: 7,014 lbf.

**Operating weight (Rubber, canopy/cab):**  
5,688 / 5,908 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
20.8 HP / 2,400 rpm  
Displacement: 68.5 cu.in.

### U35-4

- Kubota Engine (Tier IV)
- Hydraulic Angle Blade w/BOE (Opt)
- AUX1 Diverter Valve
- Deluxe Interior and Wider Entrance
- Auxiliary Circuit 1
- Adjustable Max. Oil Flow Control
- Tight Tail Swing
- Spacious Cab w/ Air Conditioning
- Auxiliary Circuit 1 (2 as option)
- Telematics Available



**Dimensions:**  
Overall length: 15'7"  
Overall height: 8'1.2"  
Overall width: 5'6.9"

**Working range:**  
Max. digging depth: 9'8.9"  
Max. digging radius @ ground: 16'11.3"  
Max. bucket breakout force: 7,924 lbf.

**Operating weight (Rubber, canopy/cab):**  
Standard blade: 8,488 / 8,810 lbs.  
Angle Blade: 8,836 / 9,158 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
24.8 HP / 2,200 rpm  
Displacement: 100.5 cu.in.

### U48-5

- Kubota Engine (Tier IV) with DPF
- Tight Tail Swing
- Hydraulic Angle Blade w/BOE (Opt)
- 7" Color Screen
- Keyless Start (Opt)
- Auxiliary Circuit 1 (2 as option)
- AUX1 Diverter Valve
- Strong Bucket and Arm Breakout Force
- Wider Cabin
- Rear-view Camera (Opt)
- Powerful Air Conditioning
- Auto-downshift Travel Motors
- Dozer Float Function
- Telematics Available



**Dimensions:**  
Overall length: 17'7"  
Overall height: 8'4"  
Overall width: 6'5"

**Working range:**  
Max. digging depth: 10'8"  
Max. digging radius @ ground: 18'4.1"  
Max. bucket breakout force: 9,304 lbf.

**Operating weight (Rubber, canopy/cab):**  
Standard blade: 12,247 / 12,456 lbs.  
Angle Blade: 11,322 / 11,531 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995): 40.4 HP / 2,200 rpm  
Displacement: 111.4 cu.in.

### U55-5

- Kubota Engine (Tier IV) with DPF
- Tight Tail Swing
- Hydraulic Angle Blade w/BOE (Opt)
- 7" Color Screen
- Keyless Start (Opt)
- Auxiliary Circuit 1 (2 as option)
- AUX1 Diverter Valve
- Strong Bucket and Arm Breakout Force
- Wider Cabin
- Rear-view Camera (Opt)
- Powerful Air Conditioning
- Auto-downshift Travel Motors
- Dozer Float Function
- Telematics Available



**Dimensions:**  
Overall length: 18'  
Overall height: 8'4"  
Overall width: 6'5"

**Working range:**  
Max. digging depth: 11'11"  
Max. digging radius @ ground: 19'7"  
Max. bucket breakout force: 10,172 lbf.

**Operating weight (Rubber, canopy/cab):**  
Standard blade: 12,247 / 12,456 lbs.  
Angle Blade: 12,721 / 12,930 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995): 47.6 HP / 2,200 rpm  
Displacement: 159.6 cu.in.

## R SERIES

### R430

- Kubota Engine (Tier IV)
- Load Sensing Transmission
- Rear Backhoe (Opt)
- Deluxe Interior (Cab)
- Powerful Air Conditioning (Cab)
- Digital Panel with Diagnostic Function
- Telematics Available



**Dimensions:**  
Overall length: 14' 3"  
Overall height: 8' 3"  
Overall width: 4' 12"

**Working range:**  
Height to hinge pin: 9' 2"  
Dump clearance: 7' 2"  
Reach fully raised: 2' 9"  
Bucket capacity: 0.5 yd<sup>3</sup>  
Tipping load (Cab/Straight): 5,743 lbs.  
(Cab/Full turn): 4,949 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
47.6 HP / 2,600 rpm  
Displacement: 111 cu.in.

### R540

- Kubota Engine (Tier IV) with DPF
- Automatic Regeneration System
- Differential Lock (100% on demand, front and rear)
- Deluxe Interior
- Full-opening Right Window
- Powerful Air Conditioning
- Multi-function Operating Lever with AUX Proportional Control
- Digital Panel with Diagnostic Function
- Telematics Available



**Dimensions:**  
Overall length: 17' 9"  
Overall height: 8' 1"  
Overall width: 5' 8"

**Working range:**  
Height to hinge pin: 10' 7"  
Dump clearance: 8' 0"  
Reach fully raised: 2' 7"  
Bucket capacity: 0.85 yd<sup>3</sup>  
Tipping load (Straight): 6,768 lbs.  
(Full turn): 5,930 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
50.9 HP / 2,400 rpm  
Displacement: 160 cu.in.

### R640

- Kubota Engine (Tier IV) with DPF
- Automatic Regeneration System
- Differential Lock (100% on demand, front and rear)
- Deluxe Interior
- Full-opening Right Window
- Powerful Air Conditioning
- Multi-function Operating Lever with AUX Proportional Control
- Digital Panel with Diagnostic Function
- Telematics Available



**Dimensions:**  
Overall length: 18' 0"  
Overall height: 8' 2"  
Overall width: 5' 11"

**Working range:**  
Height to hinge pin: 10' 8"  
Dump clearance: 7' 10"  
Reach fully raised: 2' 8"  
Bucket capacity: 0.94 yd<sup>3</sup>  
Tipping load (Straight): 7,760 lbs.  
(Full turn): 6,812 lbs.

**Engine:**  
Engine HP Gross (SAE J 1995):  
64.3 HP / 2,400 rpm  
Displacement: 160 cu.in.