



Kubota

# KUBOTA CONSTRUCTION EQUIPMENT

## LINE-UP 2024



### KX Series



**KX008-5**  
 Digging Depth: 5'8" (1,720 mm)  
 Digging Radius at Ground Level: 9'11" (3,020 mm)  
 Operating Weight: 2,315 lbs. (1,050 kg)  
 Horsepower: 10.3 (7.7 kW) / 2,050 rpm



**KX018-4**  
 Digging Depth: 7'9.7" (2,380 mm)  
 Digging Radius at Ground Level: 12'8" (3,860 mm)  
 Operating Weight: CANOPY/CAB  
 3,737 lbs. (1,695 kg) / 3,957 lbs. (1,795 kg)  
 Horsepower: 15.3 (11.4 kW) / 2,300 rpm



**KX030-4**  
 Digging Depth: 9'7" (2,980 mm)  
 Digging Radius at Ground Level: 15'9" (4,860 mm)  
 Operating Weight: CANOPY/CAB  
 6,272 lbs. (2,845 kg) / 6,426 lbs. (2,915 kg)  
 Horsepower: 24.7 (18.4 kW) / 2,250 rpm



**KX033-4**  
 Digging Depth: 10'6" (3,210 mm)  
 Digging Radius at Ground Level: 16'10" (5,120 mm)  
 Operating Weight: CANOPY/CAB  
 7,420 lbs. (3,365 kg) / 7,742 lbs. (3,511 kg)  
 Horsepower: 24.8 (18.5 kW) / 2,200 rpm  
Note: Extendable arm version available



**KX040-4**  
 Digging Depth: 11'2.7" (3,420 mm)  
 Digging Radius at Ground Level: 17'9" (5,410 mm)  
 Operating Weight: CANOPY/CAB  
 9,195 lbs. (4,170 kg) / 9,500 lbs. (4,310 kg)  
 Horsepower: 40.4 (30.1 kW) / 2,200 rpm



**KX057-5**  
 Digging Depth: 12'9" (3,875 mm)  
 Digging Radius at Ground Level: 20'1" (6,125 mm)  
 Operating Weight: CANOPY/CAB  
 12,346 lbs. (5,600 kg) / 12,577 lbs. (5,705 kg)  
 Horsepower: 47.6 (35.5 kW) / 2,200 rpm



**KX080-5**  
 Digging Depth: 15'1.1" (4,600 mm)  
 Digging Radius at Ground Level: 23'6.3" (7,170 mm)  
 Operating Weight: RUBBER/STEEL  
 18,520 lbs. (8,400 kg) / 18,760 lbs. (8,510 kg)  
 Horsepower: 66.6 (49.7 kW) / 2,000 rpm

### U Series



**U10-5**  
 Digging Depth: 5'11" (1,800 mm)  
 Digging Radius at Ground Level: 10'11" (3,330 mm)  
 Operating Weight: 2,646 lbs. (1,200 kg)  
 Horsepower: 10.3 (7.7 kW) / 2,050 rpm



**U17**  
 Digging Depth: 7'7" (2,310 mm)  
 Digging Radius at Ground Level: 12'7" (3,840 mm)  
 Operating Weight: 3,693 lbs. (1,675 kg)  
 Horsepower: 16.1 (12.0 kW) / 2,300 rpm



**U27-4**  
 Digging Depth: 9'5" (2,870 mm)  
 Digging Radius at Ground Level: 15'4" (4,680 mm)  
 Operating Weight: CANOPY/CAB  
 5,688 lbs. (2,580 kg) / 5,908 lbs. (2,680 kg)  
 Horsepower: 20.9 (15.6 kW) / 2,400 rpm



**U35-4**  
 Digging Depth: 9'8.9" (2,970 mm)  
 Digging Radius at Ground Level: 16'11.3" (5,165 mm)  
 Operating Weight: CANOPY/CAB  
 8,488 lbs. (3,850 kg) / 8,810 lbs. (3,996 kg)  
 Horsepower: 24.8 (18.5 kW) / 2,200 rpm



**U48-5**  
 Digging Depth: 10'8" (3,255 mm)  
 Digging Radius at Ground Level: 18'4" (5,585 mm)  
 Operating Weight: CANOPY/CAB  
 10,848 lbs. (4,920 kg) / 11,057 lbs. (5,015 kg)  
 Horsepower: 40.4 (30.1 kW) / 2,200 rpm

### R Series



**R55-5**  
 Digging Depth: 11'11" (3,630 mm)  
 Digging Radius at Ground Level: 19'7" (5,965 mm)  
 Operating Weight: CANOPY/CAB  
 12,247 lbs. (5,555 kg) / 12,456 lbs. (5,650 kg)  
 Horsepower: 47.6 (35.5 kW) / 2,200 rpm



**R430**  
 Operating Weight: CANOPY/CAB  
 7,758 lbs. (3,519 kg) / 8,232 lbs. (3,734 kg)  
 Bucket Capacity: 0.5 cu.yd. (0.38 m<sup>3</sup>)  
 Horsepower: 47.6 (35.5 kW) / 2,600 rpm



**R540**  
 Operating Weight: CANOPY/CAB  
 9,886 lbs. (4,485 kg) / 10,285 lbs. (4,665 kg)  
 Bucket Capacity: 0.85 cu.yd. (0.65 m<sup>3</sup>)  
 Horsepower: 50.9 (38.0 kW) / 2,400 rpm



**R640**  
 Operating Weight: CANOPY/CAB  
 11,177 lbs. (5,070 kg) / 11,563 lbs. (5,245 kg)  
 Bucket Capacity: 0.94 cu.yd. (0.72 m<sup>3</sup>)  
 Horsepower: 64.3 (48.0 kW) / 2,400 rpm



**SCL1000**  
 Rated Operating Capacity @ 35% of Tipping Load:  
 1,000 lbs. (453 kg)  
 Operating Weight: 3,035 lbs. (1,376 kg)  
 Engine Horsepower: 24.8 (18.5 kW) / 2,800 rpm

### SVL Series



**SVL65-2**  
 Rated Operating Capacity @ 35% of Tipping Load:  
 2,100 lbs. (953 kg)  
 Operating Weight: Open CAB 8,135 lbs. (3,690 kg)  
 Closed CAB 8,631 lbs. (3,915 kg)  
 Engine Horsepower: 68.4 (51.0 kW) / 2,600 rpm



**SVL75-3**  
 Rated Operating Capacity @ 35% of Tipping Load:  
 2,490 lbs. (1,129 kg)  
 Operating Weight: Open CAB 9,190 lbs. (4,169 kg)  
 Closed CAB 9,420 lbs. (4,273 kg)  
 Engine Horsepower: 96.4 (71.3 kW) / 2,400 rpm



**SVL97-2**  
 Rated Operating Capacity @ 35% of Tipping Load:  
 3,200 lbs. (1,451 kg)  
 Operating Weight: Open CAB 11,277 lbs. (5,115 kg)  
 Closed CAB 11,552 lbs. (5,240 kg)  
 Engine Horsepower: 96.4 (71.3 kW) / 2,400 rpm

### SSV Series



**SSV65**  
 Rated Operating Capacity @ 50% of Tipping Load:  
 1,950 lbs. (885 kg)  
 Operating Weight: Open CAB 7,099 lbs. (3,220 kg)  
 Closed CAB 7,319 lbs. (3,320 kg)  
 Engine Horsepower: 64.0 (47.7 kW) / 2,700 rpm



**SSV75**  
 Rated Operating Capacity @ 50% of Tipping Load:  
 2,690 lbs. (1,220 kg)  
 Operating Weight: Open CAB 8,245 lbs. (3,740 kg)  
 Closed CAB 8,466 lbs. (3,840 kg)  
 Engine Horsepower: 74.3 (55.4 kW) / 2,600 rpm