



KUBOTA CONSTRUCTION EQUIPMENT

LINE-UP 2025



KX Series



- KX008-5**
Digging Depth: 5'8" (1,720 mm)
Digging Radius at Ground Level: 9'11" (3,020 mm)
Operating Weight: 2,315 lbs. (1,050 kg)
- KX018-4**
Digging Depth: 7'9.7" (2,380 mm)
Digging Radius at Ground Level: 12'8" (3,860 mm)
Operating Weight: CANOPY/CAB 3,737 lbs. (1,695 kg) / 3,957 lbs. (1,795 kg)
- KX030-4**
Digging Depth: 9'7" (2,980 mm)
Digging Radius at Ground Level: 15'9" (4,860 mm)
Operating Weight: CANOPY/CAB 6,272 lbs. (2,845 kg) / 6,426 lbs. (2,915 kg)
- KX033-4**
Digging Depth: 10'6" (3,210 mm)
Digging Radius at Ground Level: 16'10" (5,120 mm)
Operating Weight: CANOPY/CAB 7,420 lbs. (3,365 kg) / 7,742 lbs. (3,511 kg)
Note: Extendable arm version available
- KX040-5**
Digging Depth: 11'2.3" (3,410 mm)
Digging Radius at Ground Level: 17'8.6" (5,400 mm)
Operating Weight: CANOPY/CAB 9,182 lbs. (4,165 kg) / 9,480 lbs. (4,300 kg)
- KX057-5**
Digging Depth: 12'9" (3,875 mm)
Digging Radius at Ground Level: 20'1" (6,125 mm)
Operating Weight: CANOPY/CAB 12,346 lbs. (5,600 kg) / 12,577 lbs. (5,705 kg)
- KX080-5**
Digging Depth: 15'1.1" (4,600 mm)
Digging Radius at Ground Level: 23'6.3" (7,170 mm)
Operating Weight: RUBBER/STEEL 18,520 lbs. (8,400 kg) / 18,760 lbs. (8,510 kg)

U Series



- U10-5**
Digging Depth: 5'11" (1,800 mm)
Digging Radius at Ground Level: 10'11" (3,330 mm)
Operating Weight: 2,646 lbs. (1,200 kg)
- U17-5**
Digging Depth: 7'6.2" (2,290 mm)
Digging Radius at Ground Level: 12'6.4" (3,820 mm)
Operating Weight: 3,902 lbs. (1,770 kg)
- U27-4**
Digging Depth: 9'5" (2,870 mm)
Digging Radius at Ground Level: 15'4" (4,680 mm)
Operating Weight: CANOPY/CAB 5,688 lbs. (2,580 kg) / 5,908 lbs. (2,680 kg)
- U35-4**
Digging Depth: 9'8.9" (2,970 mm)
Digging Radius at Ground Level: 16'11.3" (5,165 mm)
Operating Weight: CANOPY/CAB 8,488 lbs. (3,850 kg) / 8,810 lbs. (3,996 kg)
- U48-5**
Digging Depth: 10'8" (3,255 mm)
Digging Radius at Ground Level: 18'4" (5,585 mm)
Operating Weight: CANOPY/CAB 10,848 lbs. (4,920 kg) / 11,057 lbs. (5,015 kg)
- U55-5**
Digging Depth: 11'11" (3,630 mm)
Digging Radius at Ground Level: 19'7" (5,965 mm)
Operating Weight: CANOPY/CAB 12,247 lbs. (5,555 kg) / 12,456 lbs. (5,650 kg)

SCL Series



- SCL1000**
Rated Operating Capacity @ 35% of Tipping Load: 1,000 lbs. (453 kg)
Operating Weight: 3,035 lbs. (1,376 kg)

SVL Series



- SVL50x**
Rated Operating Capacity @ 35% of Tipping Load: 1,176 lbs. (534 kg)
Operating Weight: Open CAB 5,450 lbs. (2,472 kg)
Closed CAB 5,620 lbs. (2,549 kg)



- SVL65-2**
Rated Operating Capacity @ 35% of Tipping Load: 2,100 lbs. (953 kg)
Operating Weight: Open CAB 8,135 lbs. (3,690 kg)
Closed CAB 8,631 lbs. (3,915 kg)



- SVL75-3**
Rated Operating Capacity @ 35% of Tipping Load: 2,490 lbs. (1,129 kg)
Operating Weight: Open CAB 9,190 lbs. (4,169 kg)
Closed CAB 9,420 lbs. (4,273 kg)



- SVL97-3**
Rated Operating Capacity @ 35% of Tipping Load: 3,459 lbs. (1,569 kg)
Operating Weight: Open CAB 11,676 lbs. (5,296 kg)
Closed CAB 11,929 lbs. (5,411 kg)

SSV Series



- SSV65**
Rated Operating Capacity @ 50% of Tipping Load: 1,950 lbs. (885 kg)
Operating Weight: Open CAB 7,099 lbs. (3,220 kg)
Closed CAB 7,319 lbs. (3,320 kg)
- SSV75**
Rated Operating Capacity @ 50% of Tipping Load: 2,690 lbs. (1,220 kg)
Operating Weight: Open CAB 8,245 lbs. (3,740 kg)
Closed CAB 8,466 lbs. (3,840 kg)

R Series



- R430**
Operating Weight: CANOPY/CAB 7,758 lbs. (3,519 kg) / 8,232 lbs. (3,734 kg)
Bucket Capacity: 0.5 cu.yd. (0.38 m³)
- R540**
Operating Weight: CANOPY/CAB 9,888 lbs. (4,485 kg) / 10,285 lbs. (4,665 kg)
Bucket Capacity: 0.85 cu.yd. (0.65 m³)
- R640**
Operating Weight: CANOPY/CAB 11,177 lbs. (5,070 kg) / 11,563 lbs. (5,245 kg)
Bucket Capacity: 0.94 cu.yd. (0.72 m³)



KUBOTA TRACTOR CORPORATION

Cal. No.0001-01-05 Printed in Japan 24-12 to Q4 1,73

www.kubotaUSA.com

For Earth, For Life
Kubota